



ISO BEARING-SINGAPORE (PTE)LTD.

85,725 mm x 133,35 mm x 29,769 mm NTN
4T-497/492A tapered roller bearings



Bearing No. 4T-497/492A

4T-497/492A Bearing 2D drawings and 3D CAD models

Size	85.725x133.35x30.162 mm
Bore Diameter	85,725 mm
Outer Diameter	133,35 mm
Width	30,162 mm
d	85,725 mm
D	133,35 mm
T	30,162 mm
B	29,769 mm
C	22,225 mm
ra1 max.	3,3 mm
a	0,7 mm
Da	120 mm
db	93 mm
ra max.	3,5 mm
da	99 mm
Db	128 mm
Weight	1,43 Kg
Basic dynamic load rating (C)	129 kN
Basic static load rating (C0)	189 kN
(Grease) Lubrication Speed	2 600 r/min
(Oil) Lubrication Speed	3 500 r/min
Calculation factor (e)	0,44
Calculation factor (Y0)	0,74
d1	109.5 mm
e	0.44



ISO BEARING-SINGAPORE (PTE)LTD.

Y2	1.35
Y0	0.74
Mass	1.43 kg
Dynamic load, C	129 kN
Rating life coefficient, A2	1.4
Static load, C0	189 kN
Fatigue limit load, Cu	22.4 kN
Nlim (oil)	3,500 rpm
Nlim (grease)	2,600 rpm
Min operating temperature, Tmin	-40 ° C
Max operating temperature, Tmax	120 ° C
Characteristic cage frequency, FTF	0.45 Hz
Characteristic rolling element frequency, BSF	9.24 Hz
Characteristic outer ring frequency, BPF0	10.32 Hz
Characteristic inner ring frequency, BPF1	12.68 Hz
ra max	3.5 mm
r1a max	3.3 mm
Category	Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	1.5
Product Group	B04334